

DRYLOK® FAST PLUG®



4 lb. and 10 lb. contains handy measuring scoop

DRYLOK® Fast Plug® is a fast-setting hydraulic cement that expands as it cures and sets in just 3-5 minutes. It prevents water from flowing, even under pressure, through cracks and holes in concrete and masonry structures. It's ideal for sealing floor and wall joints, patching settlement cracks and holes in masonry walls, and anchoring metal to masonry. Similar to mortar, it sets and hardens exceptionally quick.



This product is an essential part of the waterproofing process. **1** Prepare **2** Patch **3** Waterproof

FEATURES:

- Formula:** powder
- Finish:** rough, gritty texture matching concrete
- Application tools:** putty knife, trowel, gloved hand
- Location:** interior, exterior, above or below grade, vertical, horizontal surfaces
- Where to use:** cracks and holes, floor and wall joints, settlement cracks, utility entrance holes in masonry, anchors metal to masonry
- CSI Masterformat®:** **03 01 00** MAINTENANCE OF CONCRETE
03 15 13 WATERSTOPS

BENEFITS:


- Sets in 3-5 minutes
- Stops water, even under pressure
- Patch mortar joints, floor/wall joints, cracks and holes in masonry walls
- No top-coat required
- Patches surfaces prior to applying **DRYLOK® Masonry Waterproofer**

-  **1** Application
-  **Soap and Water**
Clean up

 **16 in³**
Coverage per Lb



4 LB. 4/Case..... 00917
10 LB. 2/Case..... 00924
50 Lb. 1/Unit 00930

 **WARNING:** Cancer and Reproductive Harm – www.P65Warnings.ca.gov