DRYLOK® FLOOR & WALL MASONRY WATERPROOFER





DRYLOK® Floor & Wall Masonry Waterproofer is the first non-pigmented masonry waterproofer specifically formulated to use on bare masonry floor and wall surfaces. Provides a durable, waterproof, easy to clean, non-yellowing high gloss finish.

FEATURES:

Formula: latex base

Finish: clear, high gloss

Protection level: 31%±2% solids

Application tools: brush, roller, sprayer

(For spray specifications visit www.DRYLOK.com)

Location: interior, exterior, vertical, horizontal, below, above grade

Where to use: masonry floors, retaining walls, decorative brick and stone

facades, concrete slabs, and more*

Optional: if covering with flooring, carpeting, or a water base paint or

coating, allow final coat to dry 24 hours

Specifications: conforms to ASTM D-7088 Resistance to Hydrostatic

Pressure and ASTM D-6904 Resistance to Wind Driven Rain

CSI Masterformat®: 07 14 16 COLD FLUID-APPLIED WATERPROOFING

09 91 13 EXTERIOR PAINTING **09 91 23** INTERIOR PAINTING



90-100 Sq Ft Coverage per Gal

BENEFITS:

- GUARANTEED to stop water limited to 4 PSI to help prevent structural damage from pressure cracks
- Protects against 98 mph wind-driven rain
- Abrasion-resistant, high-gloss waterproof coating approved for floor and wall applications
- Use as a moisture vapor barrier on bare concrete floors or as a primer under latex floor paint or prior to applying floor coverings
- Reduces radon gas penetration
- Listed in Masterspec® and BSD SpecLink®



2 Hr Dry Time 2 Hr Recoat Time



100 g/L



Minimum of 2 Coats



Soap and Water Clean up





* Limitation - not for use on surfaces that are free floating such as pavers and patios or surfaces subject to automobile traffic. See DRYLOK® Penetrating Sealers for such uses



1 GAL. 2/Case......20913 5 GAL. 1/Unit20915

NOTE: COLOR SWATCH IS REPRESENTATIONAL ONLY.

WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov

